

Product data sheet Elkem Microsilica[®] HQ

Elkem ASA Silicon Products Drammensveien 169 P.O. Box 334 Skøyen NO-0213 OSLO Tel: +47 22 45 01 00 www.elkem.com

Description	Elkem Microsilica [®] is a key ingredient in advanced low and ultra-low cement castables. It is highly reactive during sintering, which leads to improved ceramic bonding at reduced firing temperatures.	
Applications	Elkem Microsilica [®] is used in castables, gunning mixes and other shaped and unshaped materials.	
Features	Elkem Microsilica [®] HQ is offered both as Undensified (HQ-U) and Densified (HQ-D).	
Benefits	 Improved flow – easier to cast Improved particle packing - denser castables Gel-bonding Improved hot-strength properties 	
Chemical analysis & physical data	Weight% SiO ₂ (diff.) C _{free} ** Fe ₂ O ₃ Al ₂ O ₃ CaO MgO K ₂ O Na ₂ O SO ₃ Cl H ₂ O *** Properties Loss on Ignition Coarse Particles >45µm pH-value Bulk density *** <u>Undensified</u> HQ-U <u>Densified</u> HQ-U <u>Densified</u> HQ-D * Test methods are available upon required *** When packed	Spec* typical 96.3 max. 0.8 max. 0.2 max. 0.5 max. 0.4 max. 0.5 max. 0.4 max. 0.5 max. 0.4 max. 0.5 max. 0.1 max. 0.8 Spec* % max. 1.5 % max. 1 5.5-7.5 kg/m ³ 250-350 kg/m ³ 450-650 est
Packaging	The product is available in 25 kg small bags and various sized big bags. Please contact our sales representative for more details.	
Storage and handling	 Avoid dust generation Store material properly, protected from moisture and contamination 	
Health, safety & environment	Please consult our Product Safety information on our website:	
	Silicon based materials TDS/SDS Finder Elkem.com	
Sustainability	For Elkem, sustainability is central to our business strategy. Our mission is to provide advanced material solutions shaping a better and more sustainable future, adding value to our stakeholders globally. We are committed to reduction in embodied carbon emission. For further information, please visit <u>www.elkem.com/sustainability/</u> or contact us to learn more about our sustainability roadmap.	
Additional information and contact	For further information, please contact our local sales representative. Our specialists will assist you in solving individual problems.	

Elkem Microsilica® is a registered trademark of Elkem ASA.

This product data sheet is property of Elkem ASA and may not without its written permission be used, copied or made available to others. The receiver is responsible for any misuse. © Copyright Elkem ASA